



BOECO BAS PLUS MODELS

Our Standard Analytical balances with automatic internal calibration

The Plus Version with: Display with enlarged characters, keypad with quick access buttons, communication interfaces 2 x USB (1 x to work with printers with PCL protocol) (and optional WIFI)

► Functions: autotest, dosing, percent weighing, totalizing, parts counting, peak hold, Newton unit measurement, statistics, checkweighing, under hook weighing, GLP procedures, animal weighing, pipettes calibration, density determination.

Menu navigation selectable in many languages

Specifiacation	BAS 31 plus	BAS 32 plus
Max. capacity	220 g	110 g
Minimal load	0,01g	0,01g
Readability	0,0001 g	0,0001 g
Tare range	- 220 g	- 110 g
Repeatability	0,0001 g	0,0001 g
Linearity	± 0,0002 g	± 0,0002 g
Pan size	∅ 100 mm	∅ 100 mm
Stabilization time	3,5 sec.	3,5 sec.
Calibration	Internal (automatic)	
Interface	2xRS232, 2xUSB(A+B), WIFI (optional)	
Display	large LCD with backlight	
Working temperature	+10°C - +40°C	
Power Supply	110-230 V AC, 50/60 Hz	
Netweight / Grossweight	5,6 kgs / 9,5 kgs	
Size / Packing size	333x206x355 / 550x460x580 mm	

Both BASplus balances are available in an optional WIFI interface version

Model	Readability	Capacity
BAS 31 plus	0,0001 g	220 g
BAS 32 plus	0,0001 g	110 g